


Geberit PE hosszú szárú ívdom



- UV álló

Alkalmazási célok

- Szennyvízelvezetéshez

Tulajdonságok

- Nagy sugár

Műszaki adatok

Alapanyag

PE-HD

Cikksz.	DN	d, ø	arc	X1	X2	K1	K2	r
367.046.16.1	100	110 mm	45 °	14.7 cm	6 cm	11 cm	2.5 cm	– cm
363.051.16.1	56	56 mm	88.5 °	21 cm	8.5 cm	17 cm	0 cm	4 cm
365.051.16.1	70	75 mm	88.5 °	21 cm	11.5 cm	14 cm	0 cm	7 cm
379.055.16.1	30	32 mm	90 °	10 cm	3 cm	7 cm	– cm	3 cm
360.055.16.1	40	40 mm	90 °	15 cm	3 cm	12 cm	– cm	3 cm
361.055.16.1	50	50 mm	90 °	18 cm	4 cm	14 cm	– cm	4 cm
363.055.16.1	56	56 mm	90 °	21 cm	4 cm	17 cm	– cm	4 cm
364.055.16.1	60	63 mm	90 °	21 cm	5 cm	16 cm	– cm	5 cm
365.055.16.1	70	75 mm	90 °	21 cm	7 cm	14 cm	– cm	7 cm
366.055.16.1	90	90 mm	90 °	24 cm	9 cm	15 cm	– cm	9 cm
367.055.16.1	100	110 mm	90 °	27 cm	10 cm	17 cm	– cm	10 cm
368.055.16.1	125	125 mm	90 °	20 cm	11 cm	9 cm	– cm	11 cm
369.055.16.1	150	160 mm	90 °	20 cm	14 cm	6 cm	– cm	14 cm



- A Geberit PE 15°-os, 30°-os, 45°-os és 88,5°-os ívdom mindkét szárán hegeszthető Geberit elektrokarmantyúval
- A Geberit PE 90°-os ívdom a hosszabbik szárán Geberit elektrokarmantyúval hegeszthető